

# eurocol

# 801

the strong connection



## EUROSTRIP EC

Self-adhesive copper strip.

### PRODUCT TYPING

Base	Electrolyte copper strip.
Format	Length 20 m. Width 10 mm. Thickness 0,1 mm.

- Self-adhesive copper tape for electrically conductive preparation of standard subfloor before installation of electrically conductive floor coverings according to floor covering manufacturer's instructions.
- Ensures transverse potential equalization according to existing standards.
- For indoor use.
- Easy application

### PROPERTIES

Special quality	self adhesive.
-----------------	----------------

### APPLICATION

Self-adhesive copper strip to accomplish an earth connection when fixing conductive floor covering.

### PROCESSING

Shelf Life	36 Months, in unopened packaging.
Remarks	Technical information and safety data sheets of any laying materials and floor coverings used must be observed and the processing conditions must be complied with. Make sure that the levelling compound under floor coverings is sufficiently thick. Eurocol 041 Europrimer EC reduces the absorbency of the substrate, therefore in the case of water vapour impermeable floor coverings, allow for correspondingly longer flash-off times for the adhesives.

*\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

#### Substrate:

- 801 Eurostrip EC is suitable for any type of subfloor that is clean, permanently dry and free from dust and grease.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

#### Instruction manual:

- Apply on floor surfaces up to 30 m<sup>2</sup>, at least 1 running metre of 801 Eurostrip EC on the with 041 Europrimer EC primed floor.
- On larger surfaces use proportionally more 801 Copper strip.
- An electrician must connect the 801 Eurostrip EC to the earth connection.
- Use for the installation of a conductive floor covering the following conductive adhesives: 615 Eurostar Lino EC for conductive linoleum and 641 Eurostar Special EC for conductive vinyl, rubber, polyolefin and carpet.

---

## ENVIRONMENT AND HEALTH

---

Safety and environment

Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste.

---

## ITEM DATA

---

### Article Definition Packaging EAN-code

801 Eurostrip EC 20 m<sup>1</sup> roll 8 710345 801010

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG173101, Version 03, Stand 2019-08-28, ersetzt Ausgabe vom 2008-07-03.